

C&I ESS

CFE-XH



Leading Technology

- Master+Slave architecture BMS with advanced AI algorithms.
- OTA upgrade capabilities & cloud platform EMS, to every RACK.
- Supports multiple inverter communications.



Flexible configuration System

- Up to 7 PACKs in series (up to 70 kWh).
- Maximum 4 RACKs in parallel to increase capacity to 280 kWh without adding other equipment.
- Industrial-Grade BMS protection & voltage level auto-matching allows free combination of series / parallel connections.
- 8000 cycles of design life to increase the return on investment in C&I energy storage scenarios.



Convenient installation

- Minimalist design and cost-saving building block installation.
- Error-proof installation with quick-connect & adaptive communication.
- PACK / RACK designed to IP65 with C5 corrosion protection.



Local Service Support

- Provides support from the design until the operation.
- Pre-sales and sales activities including online & offline product training.
- Logistics including warehousing and delivery to the installation site.
- We provide local technical support for installation, commissioning, and operation (including warranty service).

Model	CFE-XH-20	CFE-XH-30	CFE-XH-40	CFE-XH-50	CFE-XH-60	CFE-XH-70
Stacked PDU						
Model	CFE-PDU 750 - 100 - GR					
Communication Method	CAN / RS 485 / Wi-Fi					
Installation Method	Racks					
Humidity	0 – 95% RH (non-condensing)					
Altitude	≤3500 m					
Nominal Voltage	1000 Vdc					
Nominal Current	100 A (Charge & Discharge Rate of 1C)					
Size (W × D × H)	442 × 450 × 133 mm					
Rack Batteries						
Battery Type	LFP (LiFePO4)					
Model	CFE – PA102 – 100 – GR					
Capacity	20.48 kWh	30.72 kWh	40.96 kWh	51.20 kWh	61.44 kWh	71.68 kWh
Battery Voltage (PACK 102.4V)	204.8 V	307.2 V	409.6 V	512.0 V	614.4 V	716.8 V
Capacity	100 Ah					
Electrical Parameters						
Voltage Range	173 – 230 V	259 – 346 V	346 – 461 V	432 – 576 V	518 – 691 V	605 – 806 V
Max. Charging Current	100 A					
Max. Discharge Current	100 A					
Other Parameters						
Size (W × D × H)	576 × 582 × 804 mm	576 × 582 × 1034 mm	576 × 582 × 1264 mm	576 × 582 × 1494 mm	576 × 582 × 1724 mm	576 × 582 × 1954 mm
Communication Method	CAN / RS485					
Charge Operating Temperature	0 to 45 °C					
Discharge Operating Temperature	-10 to 55 °C					
Humidity	0 – 95% RH (non-condensing)					
Altitude	≤3500 m					
Installation Method	Racks & Cabinet					
Warranty & Cycle Life	10-year warranty; 8,000-cycle design life (conditions apply). (@ 25 ± 2 °C, 0.5C / 0.5C, 80% DoD)					
Transport	UN38.3 (tested) ; UN3480 as applicable					
Certificates	CE (model-dependent)					

CFE ESS Co., Ltd.

CFE has offices & warehouses in the following regions where you can get in touch with us:

Europe: Rotterdam (Netherlands) Africa: Johannesburg (South Africa)

Asia: Xi'an, Shenzhen, Tianjin, Hefei, Hong Kong (China) , and Yangon (Myanmar)

Tel: (+86) 029 38367888 Web: www.cfess.cn E-mail: cfenergy@cfess.cn