



## Application Scenarios

Factories / Data centres / Campuses / Commercial buildings / Mobile storage



### Efficient and Flexible

· LiFePO<sub>4</sub> battery storage system, two - layer battery management system.



### Intelligent Temperature Control

· Intelligent temperature control + centre-mounted industrial air - conditioning design, Balanced airflow and centre-mounted industrial air-conditioning help maintain uniform cell temperatures and Balanced airflow with centre-mounted industrial air-conditioning maintains uniform cell temperatures and reduces thermal gradients, extending battery life.



### Safe and Secure

· IP54 protection degree outdoor cube, consists of accessories, including air - cooling equipment, power distribution, fire control, etc.



### Efficient Management

· Energy management system includes cloud system & local management machine, PCS data collection and other related devices.

Model	CFE-DC100MA
Cell Type	LiFePO4 (3.2 V 100 Ah)
Total Energy	102.4 kWh
Capacity	200 Ah
Module Configuration	2P16S × 10
Usable Energy	93 kWh
Size (W × D × H)	770 × 1,125 × 2,200 mm
Battery Voltage	512 V
Voltage Range	450 - 585 V
Max. Discharge Power	60 kW
Charge and Discharge Rate	0.5 C
IP Level	IP54
Communication Method	CAN
Protection Mode	Triple Hardware Protection
Battery Protection	Over-Current / Over-Voltage / Short Circuit / Under-Voltage / Over-Temperature
Protective Class	I
Charge Operating Temperature	0 to 70 °C
Discharge Operating Temperature	-10 to 70 °C
Humidity	0 – 95% RH (non-condensing)
Altitude	≤2000m
Installation Method	Outdoor
Cooling Type	Intelligent forced-air cooling
Cycle Life	≥6,000 cycles (@25 ± 2 °C, 0.5C / 0.5C, 80% DoD)
Transport	UN38.3 (tested) ; UN3480 as applicable
Inverter Protocols Supported	Deye / SOSEN
Weight	850 kg

CFE ESS Co., Ltd.

CFE has offices & warehouses in the following regions where you can get in touch with us:

Europe: Rotterdam (Netherlands)      Africa: Johannesburg (South Africa)

Asia: Xi'an, Shenzhen, Tianjin, Hefei, Hong Kong (China) , and Yangon (Myanmar)

Tel: (+86) 029 38367888      Web: [www.cfess.cn](http://www.cfess.cn)      E-mail: [cfenergy@cfess.cn](mailto:cfenergy@cfess.cn)